


## Aufhängegarnitur

TWN 0796



Güteklasse 8 / Grade 80  
**GK8**


- + Geeignet für 3- und 4-strängige Drahtseil-Gehänge
- + Güteklasse 8
- + Von 2,8t bis 101,8t Tragfähigkeit verfügbar
- + Erfüllt EN 1677-4
- + D.N.V. 2.7-1 Typzulassung
- + Abmessungen nach DIN 5688-3 : 2007-04
- + Geeignet für Seile nach EN 13414-1
- + Dauerschwingfestigkeit: min. 20.000 Schwingspiele
- + Rückverfolgbarkeitscode
- + Extra große Übergangsglieder
- + Hochwertige Pulverbeschichtung RAL 3003
- + BG Zulassung 



geprüft auf Prüfkraft

THIELE GmbH & Co. KG  
Werkstr. 3 · 58640 Iserlohn · Germany  
THIELE.de · hebetechnik@THIELE.de

 +49 2371 947-0  
 +49 2371 947-241




# THIELE®

The **Name**  
for **Safety**.

## Master Link Assembly

TWN 0796

Güteklasse 8 / Grade 80  
**GK8**  
by THIELE

- + Suitable for 3- and 4-Leg Wire Rope Slings
- + Grade 80
- + From 2,8t up to 101,8t W.L.L. available
- + Comply with EN 1677-4
- + D.N.V. Type Approved 2.7-1.
- + Dimensions as per DIN 5688-3 : 2007-04
- + Suitable for wire ropes as per EN 13414-1
- + Minimum n°. of cycles: 20.000
- + Traceability Code
- + Extra large intermediate links
- + High value powder coating RAL 3003
- + BG approved 



Proof tested

THIELE GmbH & Co. KG  
Werkstr. 3 · 58640 Iserlohn · Germany  
THIELE.de · hebetechnik@THIELE.de

+49 2371 947-0  
+49 2371 947-241

